

ATEQ DPack

For laboratory and production line



Leak detection measurement without using gas or liquid.

ATEQ
www.ateq.com

ISO 9001
BUREAU VERITAS
Certification



CE

Mains Characteristics:

- Pressurizing packing and flow measurement
- Accuracy and repeatability of the measurement
- Friendly use
- Automatic start when the connection to the product
- Indicators results: GOOD - BAD
- Checking through a calibrated standard leak
- Traceability of measurement

Technical specifications:

- Power supply : 230 V AC / 24 V DC
- Dimensions: 380 x 250 x 136 mm
- Weight: 7 kgs
- Interface: LCD display 4 lines - Red light / Green light for pass and fail test – keyboards pads
- Technology:
 - Delta measurement across a capillary
 - Mechanical regulator adjustable in front panel
- Measurement:
 - Automatic start
 - Test time programmable (in 1/10 second)
 - Test good/bad with reject level
 - Update the test based on a set pressure
- Temperature:
 - Operation: 0°C à +45°C
 - Storage: 0°C to +60°C
- 16 programs
- RS232
- Setting:
 - Time and Date
 - 2 languages available
 - Choice of units
 - Storing the settings ...

Accessories including with instrument

- Roll of 330 adhesive foam pads (15 x 15 mm)
- 10 needles (length 400 mm x 12/10)
- Quick connect for connecting the needle