





- LRT 6000 "SPECIAL A350 TOOL"

Portable Micro-ohmmeter and loop resistance tester Combined



- → USB PORT DATA TRANSFER
- → EASY TO READ LARGE DISPLAY
- → COMBINED CLAMP ONE CLAMP DOES IT ALL!
- → MEMORY OF 2000 READINGS
- → COMPACT AND LIGHT WEIGHT(< 2 Kg)</p>

ateq.com
You
Tube

It is a very easy-to-use and versatile instrument. Its ergonomics allow the user to use it either placed on the ground or across one's shoulder or chest. A wide back-lit LCD display combined with an intuitive keyboard ensures simple and easy operation.

| GENERAL DETAILS | |
|---------------------|---|
| Presentation | 240x120x210 mm (9.4 x 4.7 x 8.3 inch) < 2kg (6lbs) |
| Internat. standards | Complies with: CE: 61010-1 ; CEM: 61326-1 and 55011 |
| Temperature | Operating: 0° to +50°C (25° to 122°F) Storage: -20° to +60°C (-4° to 140°F) Relative humidity < 90% none condensing |
| Use | Portable instrument which can be used on the ground or across one's shoulder or chest |



MAIN FEATURES

Additional battery

Additional battery charger

Small clamp CLP1, 3 m. cable supply with bag.

| Frequency/Current | 10 | 40 | 80 | 150 |
|-------------------|------------|------|----------------------|--------|
| Z (200 Hz) | $3m\Omega$ | 1 mΩ | $0,5~\text{m}\Omega$ | 0,3 mΩ |



Big clamp CLP2, 3 m. cable supply with bag.

| • | | | _ | | |
|-------------------|-------|------|------|-----|--|
| Frequency/Current | 10 | 40 | 80 | 150 | |
| Z (200 Hz) | 15 mΩ | 3 mΩ | 2 mΩ | 1mΩ | |



Probes kit

Probe and Probe head

Power

Ohm master

with 3 contacts resistance points.

Front-Bag

The LRT front bag free your hands, making it so easy to take measurements. The large LCD screen is at the right distance to be read easily.



MEASUREMENT SPECIFICATIONS IN STANDARD CONDITIONS

| | I | Loop range $m\Omega$ | Accuracy $\mu\Omega$ | RC Range | Accuracy |
|---|---|--------------------------------------|----------------------|-----------------------------|-----------------|
| Loop Resistance (Loop) | 10A AC | 0.1 to 20.00 Resolution: 0.01 | ± 10% MV +0,02 mΩ | - | - |
| Micro ohmmeter High Current (HC LF) | 10 to 150 A AC | 0.01 to 20.00 Resolution: 0.01 | ± 10% MV +0.02 mΩ | 0.1 to 500.0 Resolution: | ±10% MV +1μΩ |
| Current I | 10 to 150 A Resolution: < 100 A: 0.1 > 100A: 1 | - | ± 10% MV | - | - |
| Frequency F | 100 Hz 200 Hz | - - | ± 1% MV | - | - |

MV = Measured Value

THE ALL PACKAGE

The LRT6000 black plastic safety case, weatherproof and shock resistant, can carry all the operator needs:

- LRT6000 loop tester
- AC/DC adaptor CE plug
- Battery pack
- 1 ohm master
- Probes kit + Probes head kit
- 2 Clamps
- Winateq software
- USB cable
- Front bag
- Black case
- User manual

